

**C-1721AC**  
MPEG-4/H.264 High Definition DVB-C Receiver

**MPEG4/H.264 HD DVB-C with USB Multi-media**

**Model NO.: C-1721**



**Product Description**

Incorporating the highly integrated single chipset, C-1721AC is a high performance HD digital cable receiver supporting H.264/MPEG4 AVC decoding. C-1721AC supported **Conax CAS with user-friendly OSD (On Screen Display)** and stores up to 500 channels with fast inter-channel switching capability, which undoubtedly makes it an ideal choice for viewers like you to enjoy the digital life. High performance digital audio is also available ,including E-AC-3, HE-AAC.

**Main Features**

- Fully DVB-C(EN300429) compliant
- H.264/MPEG-4 AVC HP@L4.1, MPEG-2 MP@HL
- One touch & Schedule Recording Function
- Multiple Display Mode: 1080p/1080i/720p/576p/576i
- Aspect ratio 4:3/16:9 Selectable, Letter box, Full Screen, Auto ,Pan&Scan supported
- Electronic Program Guide for 7 Days
- Teletext Supported through VBI and OSD
- Support MPEG1/MPEG2/MPEG4/H264/VC-1/Motion JPEG(.flv/.avi/.mpg/.dat/.vob/.mov/.mkv/.ts/.trp...)
- Multi-language subtitle supported
- Program management
- Favorite program setting
- Multi-Audio supported
- Parental Control supported
- LCN supported

**Technical Specification**

- **Decoder Chipset:** MSD7C51K
- **Flash Memory:** 4MB
- **DDR RAM:** 128MB
- **Head-end**
  - ✓ **RF Connector:** F type
  - ✓ **RF Loop Through Connector:** IEC 169-2 Male
  - ✓ **Frequency Range:** 51-860MHz
  - ✓ **Signal Level:** -73 to -2dBm
  - ✓ **Demodulation:** 16/32/64/128/256QAM
- **Video Decoding**
  - H.264/AVC,MPEG-2 MP@HL,MPEG-4 SP@ASP, VC-1, RealMedia
  - ✓ **Aspect Ratio:** 4:3, 16:9
  - ✓ **Video Resolution:** 576i, 576P, 720P, 1080i,1080P
- **Audio Decoding:**
  - ✓ MPEG-1 layer I/II, MPEG-2 layer II, MP3
  - ✓ MPEG-4 AAC/AAC+ ,AC-3,E-AC-3,WMA
  - ✓ **Audio Mode:** Left/Right/Stereo
- **Terminals**
  - ✓ **Video Output:** HDMI×1, CVBS×1
  - ✓ **Audio Output:** A-L×1, A-R×1, SPDIF×1
  - ✓ **USB:** USB2.0 Port ×1
- **Power Supply**
  - ✓ **Adaptor Input Voltage Range:** AC 100~240V 50/60Hz
  - ✓ **Power Supply:** DC 5V/2 A
  - ✓ **Power consumption:** Standby <1W Working <8W

**Accessories**

- **Remote Control Unit** 1 pc.
- **User Manual** 1 pc., A5 Size, monochrome printing, Single Language
- **External infrared Sensor** 1pc

**Physical Specification**

- **Unit dimension** TBA
- **Giftbox dimension** TBA
- **Gross Weight** 0.8KG
- **Carton Package** TBA
- **Loading Quantity** TBA